

Wernhoutseweg 38A
4884 AW Wernhout
The Netherlands

└
+31 (0)76 - 59 712 20
info@vezalux.nl
www.vezalux.com

Elba pendel ball black + G125 clear



Elba pendel ball black + G125 clear			
810080.00A			
126 - CURRENT			
13-03-2025			
Daylight Italia			
Elba ball			
EG000027 - Luminaires			
EC001743 - Pendant luminaire			
Grid luminaire, Pendant luminaire, Prisms luminaire, Watertight luminaire			



Page: 1/3



IBAN NL65 INGB 0008 3845 00 BIC INGBNL2A BTW NL857194811B01 KVK 67841333 All transactions with Vezalux are subject to our general terms of trading as declared with the Chamber of Commerce at Breda 67841333.



+31 (0)76 - 59 712 20

info@vezalux.nl

Ø

www.vezalux.com



Feature

Suitable for light line configuration:	No	Light outlet:	Direct
Suitable for workplace according to EN 12464-1:	No	Direct-/indirect proportion separately controllable:	No
Lamp type:	LED exchangeable	Rated life time L70/B50 at 25 °C:	15000 h
With light source:	Yes	Rated life time L80/B10 at 25 °C:	0 h
Lamp holder:	E27	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Housing material:	Plastic	Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Housing colour:	Black	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Nominal voltage:	220 ~ 240 V	Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Nominal current:	NA mA	Degree of protection (IP):	IP20
LED nominal current at constant current:	NA mA	Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	No
Type of control gear:	Not required	Suitable for emergency lighting:	No
With control gear:	No	Emergency power supply integrated:	No
Exchangeable control gear:	No	Suitable for lamp power:	11 ~ 11 W
Dimming 0-10 V:	No	Max. system power:	0 W
Dimming 1-10 V:	No	Rated luminous flux according to IEC 62722-2-1:	1521 lm
Dimming DALI:	No	Colour of light:	White
Dimming DALI-2:	No	Luminaire efficacy:	138 lm/W
Dimming DMX:	No	Colour temperature:	2700 ~ 2700 K
Dimming programmable:	No	Colour rendering index CRI:	80-89
Dimming DSI:	No	Constant light output (CLO):	No
Dimming RF:	No	Colour of light adjustable:	No
Dimming potentiometer (integrated):	No	Luminous flux adjustable:	No
Dimming GPRS:	No	Beam angle adjustable:	No
Dimming LineSwitch:	No	Width:	0 mm
Dimming manufacturer's proprietary system:	No	Height/depth:	0 mm
Dimming mains voltage modulation:	No	Length:	175 mm
Dimming phase cut-off:	No	Diameter:	125 mm
Dimming phase cut-on:	No	With suspension:	Yes
Dimming Sine Wave Reduction:	No	Pendant length:	1500 ~ 1500 mm
Dimming Touch and Dim:	No	Conductor cross section:	0 mm²
Dimming Zigbee:	No	Connection type:	Push-in clamp
Dimming with push-button:	No	Compatible with Apple HomeKit:	No
No dim function:	Yes	Compatible with Google Assistant:	No
Light distributor:	None	Compatible with Amazon Alexa:	No
Reflector:	None	IFTTT support available:	No
Light sharing:	Symmetric		

Packaging data

Weight 0 gr

Customs code 94051041



IBAN NL65 INGB 0008 3845 00 BIC INGBNL2A BTW NL857194811B01 KVK 67841333 All transactions with Vezalux are subject to our general terms of trading as declared with the Chamber of Commerce at Breda 67841333.





Wernl
4884
The N

Wernhoutseweg 38A 4884 AW Wernhout The Netherlands ↔ +31 (0)76 - 59 712 20
info@vezalux.nl

www.vezalux.com



BTW NL857194811B01 KVK 67841333 Page: 3/3



