

Elba pendel ball brass + G125 clear



Elba pendel ball brass + G125 clear

| | |
|-----------------|---|
| Article number: | 810083.00A |
| Status product: | 126 - CURRENT |
| Changed last: | 13-03-2025 |
| Brand: | Daylight Italia |
| Type: | Elba ball |
| ETIM Group: | EG000027 - Luminaires |
| ETIM Classes: | EC001743 - Pendant luminaire |
| Synonym: | Grid luminaire, Pendant luminaire, Prisms luminaire, Watertight luminaire |



Feature

| | | | |
|---|------------------|--|----------------|
| Suitable for light line configuration: | No | Reflector: | None |
| Suitable for workplace according to EN 12464-1: | No | Light outlet: | Direct |
| Lamp type: | LED exchangeable | Direct-/indirect proportion separately controllable: | No |
| With light source: | Yes | Rated life time L70/B50 at 25 °C: | 15000 h |
| Suitable for number of light sources: | 1 | Rated life time L80/B10 at 25 °C: | 0 h |
| Lamp holder: | E27 | Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq): | 0 % |
| Housing material: | Plastic | Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq): | 0 % |
| Housing colour: | Gold | Failure rate at median useful life of 50,000 h at 25 °C ambient (tq): | 0 % |
| Nominal voltage: | 220 ~ 240 V | Failure rate at median useful life of 75,000 h at 25 °C ambient (tq): | 0 % |
| Nominal current: | 0 ~ 0 mA | Degree of protection (IP): | IP20 |
| LED nominal current at constant current: | 0 ~ 0 mA | Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24: | No |
| Type of control gear: | Not required | Suitable for emergency lighting: | No |
| With control gear: | No | Emergency power supply integrated: | No |
| Exchangeable control gear: | No | Suitable for lamp power: | 0 ~ 0 W |
| Dimming 0-10 V: | No | Max. system power: | 0 W |
| Dimming 1-10 V: | No | Rated luminous flux according to IEC 62722-2-1: | 0 lm |
| Dimming DALI: | No | Colour of light: | White |
| Dimming DALI-2: | No | Luminaire efficacy: | 0 lm/W |
| Dimming DMX: | No | Colour temperature: | 2700 ~ 2700 K |
| Dimming programmable: | No | Colour rendering index CRI: | 90-100 |
| Dimming DSI: | No | Constant light output (CLO): | No |
| Dimming RF: | No | Colour of light adjustable: | No |
| Dimming potentiometer (integrated): | No | Luminous flux adjustable: | No |
| Dimming GPRS: | No | Beam angle adjustable: | No |
| Dimming LineSwitch: | No | Width: | 0 mm |
| Dimming manufacturer's proprietary system: | No | Height/depth: | 0 mm |
| Dimming mains voltage modulation: | No | Length: | 175 mm |
| Dimming phase cut-off: | Yes | Diameter: | 125 mm |
| Dimming phase cut-on: | No | With suspension: | Yes |
| Dimming Sine Wave Reduction: | No | Pendant length: | 1500 ~ 1500 mm |
| Dimming Touch and Dim: | No | Conductor cross section: | 0 mm² |
| Dimming Zigbee: | No | Compatible with Apple HomeKit: | No |
| Dimming with push-button: | No | Compatible with Google Assistant: | No |
| No dim function: | No | Compatible with Amazon Alexa: | No |
| Light distributor: | None | IFTTT support available: | No |

Packaging data

| | |
|--------------|----------|
| Weight | 0 gr |
| Customs code | 94051041 |

