

## Ledvance LED CLASSIC P 25 DIM P 2.8W 827 Frosted E14



Dimmable LED lamps, mini-ball shape. Product features: Professional LED lamps for line voltage. Dimmable. Lifetime: up to 15,000 h. Beam angle: up to 300°. Lamp made of glass. Good color rendering (Ra ? 80) and color stability throughout the life of the lamp. Product benefits: Design, dimensions, luminous flux comparable to an incandescent lamp. Lower energy consumption than incandescent or halogen lamps. Robust against vibrations. Lamps with innovative LED "filament" technology. Instant 100 % light, no warm-up time. Can be easily fitted instead of ordinary light bulbs. Areas of application: Perfect for decorative installations. Domestic applications. General illumination. Outdoor use in suitable outdoor luminaires only.

Article number:	LV 067662
Status product:	126 - CURRENT
Changed last:	01-08-2024
Brand:	LEDVANCE
Type:	LED ball lamp
ETIM Group:	EG000028 - Lamps
ETIM Classes:	EC001959 - LED-lamp/Multi-LED
Synonym:	Bulblamp, Candlelamp, Globelamp, Lamp, LED, LED candle, LED capsule, LED lamp, LED luster



## Feature

Nominal voltage:	220 ~ 240 V	Colour consistency (McAdam ellipse):	SDCM6
Nominal current:	13 ~ 13 mA	Dimmable:	No
Power factor:	0.5	Diameter:	45 mm
Lamp power:	2.8 ~ 2.8 W	Length:	78 mm
Voltage type:	AC	Degree of protection (IP):	IP20
Luminous flux:	250 ~ 250 lm	Energy Efficiency Index (EEI):	0.13
Rated luminous flux according to IEC 62612:	250 lm	Min. number of switching cycles:	100000
Lamp efficacy:	89 lm/W	Weighted energy consumption in 1000 hours:	3 kWh
Luminous intensity:	0 cd	Average nominal lifespan:	15000 h
Colour rendering index CRI:	80-89	Remote operation possible:	No
Lamp shape:	Pear-shape	With remote control:	No
Filament lamp:	Yes	Photobiological safety according to EN 62471:	RG0
Type of glass/cover:	Clear	Compatible with Apple HomeKit:	No
Colour of light according to EN 12464-1:	Warm white <3300 K	Compatible with Google Assistant:	No
Socket:	E14	Compatible with Amazon Alexa:	No
Colour temperature:	2700 ~ 2700 K	IFTTT support available:	Yes
Beam angle:	320 ~ 320 °		

## Packaging data

Weight	0.02 kg
Width	0.05 m
Height	0.09 m
Length	0.05 m
Customs code	85395200

