

## DULUX LED T/E HF & AC MAINS V 7W 840 GX24Q-2



LED replacement for CFLni with 4-pin GX24q base for ECG and AC mains operation. Product features: LED replacement for conventional compact fluorescent lamps for use in ECG luminaires or on AC mains. Lifetime: up to 30,000 h. Single-ended four-pin plug-in GX24q base. Rotatable base around its longitudinal axis ( $\pm 90^\circ$ ). Type of protection: IP20. Mercury-free lamps. Product benefits: Easy installation. Low energy consumption. Easy relamping thanks to compact design. Operation directly on 230 V AC mains possible. Areas of application: General illumination within ambient temperatures from  $-20 \dots +45^\circ\text{C}$ . Supermarkets and department stores. Walkways and corridors. Hotels, restaurants. Safety advice: Always check the latest update of the compatibility list available on [www.ledvance.com/ecg-compatibility](http://www.ledvance.com/ecg-compatibility). Not suitable for operation with conventional control gear.. The operating temperature range of DULUX LED is restricted. In case of doubt r

Article number:	LV 822276
Status product:	126 - CURRENT
Changed last:	10-02-2025
Brand:	LEDVANCE
Type:	GX24Q
ETIM Group:	EG000028 - Lamps
ETIM Classes:	EC001959 - LED-lamp/Multi-LED
Synonym:	Bulblamp, Candlelamp, Globelamp, Lamp, LED, LED candle, LED capsule, LED lamp, LED luster



## Feature

Nominal voltage:	220 ~ 240 V	Beam angle:	120 ~ 120 °
Nominal current:	32 ~ 32 mA	Colour consistency (McAdam ellipse):	SDCM6
Power factor:	0.9	Dimmable:	No
Lamp power:	7 ~ 7 W	Diameter:	45 mm
Voltage type:	AC	Length:	119.8 mm
Luminous flux:	800 ~ 800 lm	Degree of protection (IP):	IP20
Rated luminous flux according to IEC 62612:	800 lm	Min. number of switching cycles:	200000
Lamp efficacy:	114 lm/W	Weighted energy consumption in 1000 hours:	7 kWh
Colour rendering index CRI:	80-89	Average nominal lifespan:	30000 h
Lamp shape:	Tube, single-ended	Remote operation possible:	No
Filament lamp:	No	With remote control:	No
Type of glass/cover:	Frosted	Photobiological safety according to EN 62471:	RG0
Colour of light according to EN 12464-1:	Neutral white 3300-5300 K	Compatible with Apple HomeKit:	No
Socket:	Other	Compatible with Google Assistant:	No
Colour:	White	Compatible with Amazon Alexa:	No
Colour temperature:	4000 ~ 4000 K	IFTTT support available:	Yes
Housing colour:	White		

## Packaging data

Weight	0.12 kg
Width	0.05 m
Height	0.13 m
Length	0.05 m
Customs code	85395200

