

Wernhoutseweg 38A 4884 AW Wernhout The Netherlands Section 3.1 (0)76 - 59 712 20
Section 3.1

Osram LED PIN MICRO 12 V 1W 827 Clear G4



Small sized low-voltage 12 V LED lamps with retrofit pin base. Product features: Compatible with many common conventional and electronic control gears (see also <u>compatibility list</u>). LED alternative to low voltage halogen lamps. Base: G4. Product benefits: Extremely small dimensions. Variable use at Direct Current and Alternating Current. Good all-around light emission. Ideal for decorative and free-burning applications. Long lifetime of up to 15,000 h. Three year guarantee. Areas of application: Decorative applications. Atmospheric accent lighting throughout the home. Outdoor use in suitable outdoor luminaires only.

OSR 523098 126 - CURRENT 19-06-2024
19-06-2024
OSRAM
G4
EG000028 - Lamps
EC001959 - LED-lamp/Multi-LED
Bulblamp, Candlelamp, Globelamp, Lamp, LED, LED candle, LED capsule, LED lamp, LED luster



Page: 1/3



IBAN NL65 INGB 0008 3845 00 BIC INGBNL2A BTW NL857194811B01 KVK 67841333 All transactions with Vezalux are subject to our general terms of trading as declared with the Chamber of Commerce at Breda 67841333.



Wernhoutseweg 38A

+31 (0)76 - 59 712 20

info@vezalux.nl

www.vezalux.com Ø



Feature

Nominal voltage:	12 ~ 12 V	Dimmable:	No
Nominal current:	130 ~ 130 mA	Diameter:	10 mm
Power factor:	0.5	Length:	30 mm
Lamp power:	1 ~ 1 W	Degree of protection (IP):	IP20
Voltage type:	AC/DC	Energy Efficiency Index (EEI):	0.11
Luminous flux:	100 ~ 100 lm	Lamp designation:	Other
Rated luminous flux according to IEC 62612:	100 lm	Energy efficiency class:	F
Lamp efficacy:	100 lm/W	Min. number of switching cycles:	100000
Colour rendering index CRI:	80-89	Total harmonic distortion:	180
Lamp shape:	Other	Weighted energy consumption in 1000 hours:	1 kWh
Filament lamp:	No	Average nominal lifespan:	15000 h
Type of glass/cover:	Clear	Remote operation possible:	No
Colour of light according to EN 12464-1:	Warm white <3300 K	With remote control:	No
Socket:	G4	Photobiological safety according to EN 62471:	RG1
Colour:	Multi-coloured	Compatible with Apple HomeKit:	No
Colour temperature:	2700 ~ 2700 K	Compatible with Google Assistant:	No
Beam angle:	320 ~ 320 °	Compatible with Amazon Alexa:	No
Colour consistency (McAdam ellipse):	SDCM6	IFTTT support available:	Yes

Packaging data

Weight	0.01 kg
Width	0.05 m
Height	0.1 m
Length	0.02 m
Customs code	85395200



BTW NL857194811B01 KVK 67841333


Page: 2/3



Wernhoutseweg 38A
4884 AW Wernhout
The Netherlands

(₀)76 - 59 712 20
info@vezalux.nl

www.vezalux.com





BTW NL857194811B01 KVK 67841333 Page: 3/3

All transactions with Vezalux are subject to our general terms of trading as declared with the Chamber of Commerce at Breda 67841333.