

PARATHOM® LINE R7s 78.00 mm 75 8.2 W/2700 K R7s



Double-ended special LED lamps. Product features: LED alternative to conventional R7s lamps. Good quality of light; color rendering index Ra: ? 80; constant chromaticity. Product benefits: Fits into most R7s luminaires thanks to excentric base. Good all-around light emission. Long lifetime of up to 15,000 h. Lower thermal output (compared with the standard reference product). Four year guarantee. Areas of application: General illumination within ambient temperatures from -20...+40 °C. Hospitality. Domestic applications. Outdoor use in suitable outdoor luminaires only.

Article number:	LV 653221
CHANGED_LAST:	29-11-2023
Brand:	OSRAM
Type:	recessed spot
ETIM Group:	EG000028 - Lamps
ETIM Classes:	EC001959 - LED-lamp/Multi-LED
SYNONYM:	Bulblamp, Candlelamp, Globelamp, Lamp, LED, LED candle, LED capsule, LED lamp, LED luster



Feature

Nominal voltage:	220 ~ 220 V	Colour consistency (McAdam ellipse):	SDCM6
Nominal current:	57 ~ 57 mA	Dimmable:	No
Power factor:	0.5	Diameter:	29 mm
Lamp power:	8.2 ~ 8.2 W	Length:	78 mm
Voltage type:	AC	Degree of protection (IP):	IP20
Luminous flux:	1055 ~ 1055 lm	Lamp designation:	Other
Rated luminous flux according to IEC 62612:	1055 lm	Energy efficiency class:	E
Lamp efficacy:	128 lm/W	Min. number of switching cycles:	100000
Luminous intensity:	0 cd	Total harmonic distortion:	110
Colour rendering index CRI:	80-89	Weighted energy consumption in 1000 hours:	9 kWh
Lamp shape:	Tube, double-ended	Average nominal lifespan:	15000 h
Filament lamp:	No	Remote operation possible:	No
Type of glass/cover:	Clear	With remote control:	No
Colour of light according to EN 12464-1:	Warm white <3300 K	Photobiological safety according to EN 62471:	RG0
Socket:	R7s	Compatible with Apple HomeKit:	No
Colour:	White	Compatible with Google Assistant:	No
Colour temperature:	2700 ~ 2700 K	Compatible with Amazon Alexa:	No
Housing colour:	White	IFTTT support available:	No
Beam angle:	330 ~ 330 °		

Packaging data

Weight	0.04 kg
Width	0.03 m
Height	0.08 m
Length	0.03 m
Customs code	85395200

