

LED B22d 27x58 mm 24-30V 4.5W 830 550LM



> 2 year warranty; Quality higher than average in the market; High lumen with compact size; Suitable for 24V with over voltage protection ; Perfect incandescent replacement by size and lumen; Marine and automotive application;

Article number:	L222758430
Status product:	126 - CURRENT
Changed last:	07-02-2025
Brand:	Schiefer
Type:	B22d
ETIM Group:	EG000028 - Lamps
ETIM Classes:	EC001959 - LED-lamp/Multi-LED
Synonym:	Bulblamp, Candlelamp, Globelamp, Lamp, LED, LED candle, LED capsule, LED lamp, LED luster



Feature

Nominal voltage:	24 ~ 30 V	Dimmable:	No
Nominal current:	150 ~ 188 mA	Diameter:	27 mm
Power factor:	0.6	Length:	58 mm
Lamp power:	4.5 ~ 4.5 W	Degree of protection (IP):	IP20
Voltage type:	AC/DC	Energy Efficiency Index (EEI):	0.1
Luminous flux:	495 ~ 605 lm	Lamp designation:	Other
Rated luminous flux according to IEC 62612:	550 lm	Energy efficiency class:	E
Lamp efficacy:	122.22 lm/W	Min. number of switching cycles:	50000
Colour rendering index CRI:	80-89	Weighted energy consumption in 1000 hours:	5 kWh
Lamp shape:	Tube, single-ended	Average nominal lifespan:	30000 h
Filament lamp:	No	Remote operation possible:	No
Type of glass/cover:	Clear	With remote control:	No
Colour of light according to EN 12464-1:	Warm white <3300 K	Photobiological safety according to EN 62471:	RG0
Socket:	B22d	Compatible with Apple HomeKit:	No
Colour:	White	Compatible with Google Assistant:	No
Colour temperature:	3000 ~ 3000 K	Compatible with Amazon Alexa:	No
Beam angle:	360 ~ 360 °	IFTTT support available:	No
Colour consistency (McAdam ellipse):	SDCM5		

Packaging data

Weight	0.04 kg
Width	0.03 m
Height	0.07 m
Length	0.03 m
Customs code	85395200

