

LED G53 AR111x67 12V 12W 690Lm 927 10Degr. AC/DC Dim



> CRI90; > 2 year warranty; SDCM3; Dimmable; Special (decorative) design for all markets;
Suitable for high quality projects;

Article number:	LAR11121292710D
Status product:	126 - CURRENT
Changed last:	07-02-2025
Brand:	Schiefer
Type:	LED spot AR111
ETIM Group:	EG000028 - Lamps
ETIM Classes:	EC001959 - LED-lamp/Multi-LED
Synonym:	Bulblamp, Candlelamp, Globelamp, Lamp, LED, LED candle, LED capsule, LED lamp, LED luster



Feature

Nominal voltage:	10 ~ 14 V	Colour consistency (McAdam ellipse):	SDCM3
Nominal current:	857 ~ 1200 mA	Dimmable:	Yes
Power factor:	0.9	Diameter:	111 mm
Lamp power:	12 ~ 12 W	Length:	67 mm
Voltage type:	AC/DC	Degree of protection (IP):	IP20
Luminous flux:	585 ~ 715 lm	Energy Efficiency Index (EEI):	0.22
Rated luminous flux according to IEC 62612:	650 lm	Lamp designation:	AR111
Lamp efficacy:	54.17 lm/W	Energy efficiency class:	G
Luminous intensity:	7900 cd	Min. number of switching cycles:	30000
Colour rendering index CRI:	90-100	Weighted energy consumption in 1000 hours:	12 kWh
Lamp shape:	Reflector	Average nominal lifespan:	25000 h
Filament lamp:	No	Remote operation possible:	No
Type of glass/cover:	Clear	With remote control:	No
Colour of light according to EN 12464-1:	Warm white <3300 K	Photobiological safety according to EN 62471:	RG0
Socket:	G53	Compatible with Apple HomeKit:	No
Colour:	White	Compatible with Google Assistant:	No
Colour temperature:	2700 ~ 2700 K	Compatible with Amazon Alexa:	No
Housing colour:	Grey	IFTTT support available:	No
Beam angle:	10 ~ 10 °		

Packaging data

Weight	0.18 kg
Width	0.14 m
Height	0.09 m
Length	0.14 m
Customs code	85395200

