

3-Phase DIN Energy Meter 100A Thorgeon



3-Phase DIN Energy Meter 100A Thorgeon	
Article number:	TH 01003
Status product:	126 - CURRENT
Changed last:	19-12-2024
Brand:	Thorgeon
Type:	Energy meter 3-Phase DIN
ETIM Group:	EG000045 - Meters
ETIM Classes:	EC001506 - Kilowatt-hour meter
Synonym:	Effective power meter, Electricity meter for service distribution board, Energy meter, Four-conductor pulse generator meter, Four-conductor value transformer pulse generator meter, Kilowatt-hour meter, Mechanical kilowatt-hour meter, Rate meter, Rotary current four-conductor meter



Feature

Type of meter:	Electronic	Approval:	Measuring Instruments Directive
Nominal current (In):	5 A	Pulse output:	Electrical
Max. current (Imax):	100 A	Pulse type:	S0
Nominal voltage (Un) N-L:	230 ~ 400 V	Pulse rate:	400 ~ 400 Imp/kWh (kvarh)
Nominal voltage (Un) L-L:	0 ~ 0 V	Type of indication:	Digital
Frequency:	50 ~ 60 Hz	Mounting method:	DRA (DIN-rail adapter)
Accuracy class:	B	Width in number of modular spacings:	75
Pole type:	Three conductor	Width:	75 mm
Model:	Direct measurement	Depth:	65 mm
Energy type:	Effective power	Height:	103 mm
Suitable for:	Purchase	Type of interface:	None
Tariff type:	One-tariff	EEC40 signature:	No
Tariff control:	Internal	With lock code:	No
Measurement type load profile:	No	Degree of protection (IP):	IP20
Escapement mechanism:	No	Degree of protection (NEMA):	Other
Calibrated:	No		

Packaging data

Weight	0.39 kg
Width	80 mm
Height	71 mm
Length	110 mm
Customs code	90283019

