

LED emergency 220-240V 5W 6000K 3hrs. battery Thorgeon



LED emergency 220-240V 5W 6000K 3hrs. battery Thorgeon

Article number:	TH 03028
Status product:	126 - CURRENT
Changed last:	10-04-2025
Brand:	Thorgeon
Type:	Escape Route
ETIM Group:	EG000027 - Luminaires
ETIM Classes:	EC001957 - Emergency luminaire
Synonym:	Emergency luminaire, Transparent



Feature

Mounting method:	Wall surface mounting/ceiling surface mounting	Degree of protection (IP):	IP65
Function:	Escape route signage	Protection class:	II
With pictogram:	Yes	Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	No
With remote switch connection:	No	Rated ambient temperature according to IEC 62722-2-1:	0 ~ 0 °C
With remote control:	No	Max. system power:	5 W
Battery quality:	Lithium-ions	Rated luminous flux according to IEC 62722-2-1:	0 lm
Lamp type:	LED not exchangeable	Luminous flux in standby mode:	50 lm
With light source:	Yes	Colour temperature:	6000 ~ 6500 K
Housing material:	Other	Power factor:	0.4
Housing colour:	White	Recognition distance:	30 m
Voltage type:	AC	Nominal operation time:	3 ~ 3 h
Nominal voltage:	220 ~ 240 V	Width:	310 mm
LED nominal current at constant current:	25 ~ 65 mA	Height/depth:	135.9 mm
Exchangeable control gear:	No	Length:	63.3 mm
Rated life time L70/B50 at 25 °C:	0 h	Outer diameter:	0 mm
Rated life time L80/B10 at 25 °C:	0 h	Built-in width:	0 mm
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %	Built-in height/depth:	0 mm
Lumen maintenance at median useful life of 100,000 h at 25 °C ambient (tq):	0 %	Built-in length:	0 mm
Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %	Built-in diameter:	0 mm
Failure rate at median useful life of 100,000 h at 25 °C ambient (tq):	0 %	Conductor cross section:	0 mm²
Constant light output (CLO):	No		

Packaging data

Weight	0.92 kg
Width	362 mm
Height	310 mm
Length	470 mm
Customs code	85395100

