

Panic emergency LED light 10in1 3H 3W 5000K 240Lm IP20 Thorgeon



Panic emergency LED light 10in1 3H 3W 5000K 240Lm IP20 Thorgeon

Article number: TH 03084

CHANGED_LAST: 29-11-2023

Brand: Thorgeon

Type: Panic Emergency light

ETIM Group: EG000027 - Luminaires

ETIM Classes: EC001957 - Emergency luminaire

SYNONYM: Emergency luminaire, Transparent



Feature

Mounting method:	Surface mounting/recessed mounting	Degree of protection (IP):	IP20
With pictogram:	No	Degree of protection (NEMA):	1
Monitoring equipment:	Test button	Impact strength:	IK06
With remote switch connection:	No	Protection class:	II
With remote control:	No	Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	No
Lamp type:	LED not exchangeable	Rated ambient temperature according to IEC 62722-2-1:	0 ~ 0 °C
With light source:	Yes	Max. system power:	3 W
Suitable for number of light sources:	1	Rated luminous flux according to IEC 62722-2-1:	240 lm
Lamp holder:	None	Luminous flux in standby mode:	0 lm
Housing material:	Plastic	Colour temperature:	5000 ~ 5000 K
Housing colour:	White	Power factor:	0.3
Material cover:	Without cover	Recognition distance:	0 m
Voltage type:	AC	Nominal operation time:	3 ~ 3 h
Nominal voltage:	220 ~ 240 V	Width:	0 mm
LED nominal current at constant current:	585 ~ 585 mA	Height/depth:	62 mm
Type of control gear:	Electronic transformer	Length:	0 mm
Exchangeable control gear:	Yes	Outer diameter:	140 mm
Light distributor:	Diffuser lens/optic/panel	Built-in width:	0 mm
Rated life time L70/B50 at 25 °C:	50000 h	Built-in height/depth:	0 mm
Rated life time L80/B10 at 25 °C:	0 h	Built-in length:	0 mm
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %	Built-in diameter:	0 mm
Lumen maintenance at median useful life of 100,000 h at 25 °C ambient (tq):	0 %	Type of wiring:	Ending
Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %	Conductor cross section:	0 mm²
Failure rate at median useful life of 100,000 h at 25 °C ambient (tq):	0 %	Connection type:	Other
Constant light output (CLO):	Yes		

Packaging data

Weight	0.52 kg
Width	145 mm
Height	68 mm
Length	150 mm
Customs code	94054940

