

Wernhoutseweg 38A 4884 AW Wernhout The Netherlands

0

## ILLU Cable E27 51.5m 50 bases IP44 -1m- Thorgeon



ILLU Cable E27 51.5m 50 bases IP44 -1m- Tho	orgeon
Article number:	TH 14008
CHANGED_LAST:	29-11-2023
Brand:	Thorgeon
Туре:	50m 50 lamp holders
ETIM Group:	EG000027 - Luminaires
ETIM Classes:	EC002761 - Festive lighting
SYNONYM:	Bulb luminaire, Candle, Candle stick light, Chandelier, Christmas lighting, Christmas tree lighting, Curtain light, Festive lighting, Illumination cable set



Page: 1/3



IBAN NL65 INGB 0008 3845 00 BIC INGBNL2A BTW NL857194811B01 KVK 67841333 All transactions with Vezalux are subject to our general terms of trading as declared with the Chamber of Commerce at Breda 67841333.



S 2

Ø

+31 (0)76 - 59 712 20 info@vezalux.nl

www.vezalux.com



## Feature

ModelIllumination cable setHighest energy efficiency class of the exchangeable lange)DescriptionNumber of light points000Lamp typeOtherRated life time L70/B50 at 25 °c0 hWith light sourceNoLumen maintenance at median useful life of 50,000 h at 25 °c ambient (nt)0Voltage typeAFailure rate at median useful life of 50,000 h at 25 °c ambient (nt)0Over Constant light output (DC)000Over Constant light output (DC) <th></th> <th></th> <th></th> <th></th>				
Number of light points:50Lowest energy efficiency class of the exchangeable lamp: exchangeable lamp:ALamp type:OtherRated life time L70/B50 at 25 °C: 0 h0 hWith light source:NoLumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):0 %Voltage type:ACFailure rate at median useful life of 50,000 h at 25 °C ambient (tq):0 %OtherNoConstant light output (CLO):NoNominal voltage:0 ~ 0 VConstant light output (CLO):NoConnected load:2000 WDegree of protection (IP):IP44Battery power supply:NoProtection class:IISuitable for outdoor use:YesColour of lightMulti-colouredWith power bridge:NoWithO mmType of control gear:NoDiameter:0 mmExchangeable control gear:NoDiameter:0 mmEnergy efficiency class of the built-in lamp:OtherConductor cross sectio:0 mm	Model:	Illumination cable set		D
Lamp type:OtherRated life time L70/B50 at 25 °C:0 hWith light source:NoLumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):0 %Voltage type:ACFailure rate at median useful life of 50,000 h at 25 °C ambient (tq):0 %Nominal voltage:0 ~ 0 VConstant light output (CLO):NoConnected load:2000 WDegree of protection (IP):IP44Battery power supply:NoProtection class:ISuitable for outdoor use:YesColour of light:Multi-colouredCouplable:YesHeight/depth:0 mmType of control gear:Not requiredTotal length:51.5 mEnergy efficiency class of the built-in lamp:OtherConductor cross section:0 mm <sup>2</sup>				
With light source:NoLumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):0 %Voltage type:ACFailure rate at median useful life of 50,000 h at 25 °C ambient (tq):0 %Nominal voltage:0 ~ 0 VConstant light output (CLO):NoConnected load:200 WDegree of protection (IP):IP44Battery power supply:NoProtection class:IISuitable for outdoor use:YesColour of light:0 mmCouplable:YesHeight/depth:0 mmType of control gear:Not requiredTotal length:51.5 mEnergy efficiency class of the built-in lamp:OtherConductor cross section:0 mm <sup>2</sup>	Number of light points:	50		A
Solution       Solution <td< td=""><td>Lamp type:</td><td>Other</td><td>Rated life time L70/B50 at 25 °C:</td><td>0 h</td></td<>	Lamp type:	Other	Rated life time L70/B50 at 25 °C:	0 h
25 °C ambient (tq):         Nominal voltage:       0 ~ 0 V         Connected load:       2000 W         Degree of protection (IP):       IP44         Battery power supply:       No         Not protection class:       II         Suitable for outdoor use:       Yes         Vith power bridge:       No         Not required       Mot required         Yes       Motie         O mm       Omm         Suitable for outdoor use:       Yes         Yes       Motie         O nom       Omm         Couplable:       Yes         Type of control gear:       Not required         Not required       Conductor cross section:         Energy efficiency class of the built-in lamp:       Other         Energy efficiency class of the provided       A+	With light source:	No		0 %
Connected load:2000 WDegree of protection (IP):IP44Battery power supply:NoProtection class:ISuitable for outdoor use:YesColour of light:Multi-colouredWith power bridge:NoWidth:0 mmCouplable:YesHeight/depth:0 mmCouplable:YesTotal length:51.5 mExchangeable control gear:NoDiameter:0 mmEnergy efficiency class of the built-in lamp:OtherConductor cross section:0 mm²	Voltage type:	AC		0 %
Battery power supply:NoProtection class:IISuitable for outdoor use:YesColour of light:Multi-colouredWith power bridge:NoWidth:0 mmCouplable:YesHeight/depth:0 mmCouplable:YesHeight/depth:0 mmType of control gear:Not requiredTotal length:51.5 mEnergy efficiency class of the built-in lamp:OtherConductor cross section:0 mm²Energy efficiency class of the providedA+A+A	Nominal voltage:	0 ~ 0 V	Constant light output (CLO):	No
Suitable for outdoor use:YesColour of light:Multi-colouredWith power bridge:NoWidth:0 mmCouplable:YesHeight/depth:0 mmType of control gear:Not requiredTotal length:51.5 mEnergy efficiency class of the built-in lamp:OtherConductor cross section:0 mm²Energy efficiency class of the providedA+Conductor cross section:0 mm²	Connected load:	2000 W	Degree of protection (IP):	IP44
With power bridge:NoWidth:0 mmCouplable:YesHeight/depth:0 mmType of control gear:Not requiredTotal length:51.5 mExchangeable control gear:NoDiameter:0 mmEnergy efficiency class of the built-in lamp:OtherConductor cross section:0 mm <sup>2</sup> Energy efficiency class of the providedA+Conductor cross section:Conductor cross section:	Battery power supply:	No	Protection class:	II
Couplable:       Yes       Height/depth:       0 mm         Type of control gear:       Not required       Total length:       51.5 m         Exchangeable control gear:       No       Diameter:       0 mm         Energy efficiency class of the built-in lamp:       Other       Conductor cross section:       0 mm <sup>2</sup> Energy efficiency class of the provided       A+	Suitable for outdoor use:	Yes	Colour of light:	Multi-coloured
Type of control gear:       Not required       Total length:       51.5 m         Exchangeable control gear:       No       Diameter:       0 mm         Energy efficiency class of the built-in lamp:       Other       Conductor cross section:       0 mm <sup>2</sup> Energy efficiency class of the provided       A+	With power bridge:	No	Width:	0 mm
Exchangeable control gear:     No     Diameter:     0 mm       Energy efficiency class of the built-in lamp:     Other     Conductor cross section:     0 mm <sup>2</sup> Energy efficiency class of the provided     A+	Couplable:	Yes	Height/depth:	0 mm
Energy efficiency class of the built-in lamp: Other Conductor cross section: 0 mm <sup>2</sup> Energy efficiency class of the provided A+	Type of control gear:	Not required	Total length:	51.5 m
Energy efficiency class of the provided A+	Exchangeable control gear:	No	Diameter:	0 mm
	Energy efficiency class of the built-in lamp:	Other	Conductor cross section:	0 mm²
		A+		

## Packaging data

Weight	10.35 kg
Width	220 mm
Height	260 mm
Length	450 mm
Customs code	85366110

BTW NL857194811B01 KVK 67841333 Page: 2/3



Wernhoutseweg 38A
 4884 AW Wernhout
 The Netherlands

↔ +31 (0)76 - 59 712 20
 info@vezalux.nl

www.vezalux.com



IBAN NL65 INGB 0008 3845 00 BIC INGBNL2A BTW NL857194811B01 KVK 67841333 Page: 3/3



