

# Pliable Corrugated Conduit with Pulling Wire 50m 25mm 750N G



|                                                              |                                                                                      |
|--------------------------------------------------------------|--------------------------------------------------------------------------------------|
| Pliable Corrugated Conduit with Pulling Wire 50m 25mm 750N G |                                                                                      |
| Article number:                                              | TH 15059                                                                             |
| Status product:                                              | 126 - CURRENT                                                                        |
| Changed last:                                                | 11-12-2024                                                                           |
| Brand:                                                       | Thorgeon                                                                             |
| Type:                                                        | Flexible installation pipe with Pulling Wire                                         |
| ETIM Group:                                                  | EG000002 - Pipes/hoses for cable installation                                        |
| ETIM Classes:                                                | EC001174 - Plastic installation tube                                                 |
| Synonym:                                                     | Installation tube, Pipe, Plastic installation tube, Plastic pipe, Plastic tube, Tube |



## Feature

|                                        |                    |                                                |             |
|----------------------------------------|--------------------|------------------------------------------------|-------------|
| Material:                              | PVC, UV-stabilized | Machine and systems installation:              | Yes         |
| Halogen free:                          | No                 | Suitable for underfloor installation (screed): | Yes         |
| Fire retardant version:                | No                 | Outdoor installation:                          | Yes         |
| Bending strength:                      | Pliable            | Suitable for underground installation:         | No          |
| With sleeve:                           | No                 | Inner diameter:                                | 19 mm       |
| Compressive strength class:            | Medium (class 3)   | Outer diameter:                                | 25 mm       |
| Impact strength:                       | Medium (class 3)   | Operating temperature:                         | -15 ~ 60 °C |
| Flush-mounted installation:            | Yes                | High conducting inner coating:                 | No          |
| Surface mounting:                      | Yes                | With metre indication:                         | No          |
| Suitable for installation on wood:     | Yes                | Colour:                                        | Grey        |
| Suitable for hollow wall installation: | Yes                | RAL-number:                                    | 7035        |
| Suitable for concrete installation:    | Yes                |                                                |             |

## Packaging data

|              |          |
|--------------|----------|
| Weight       | 0 gr     |
| Customs code | 85444991 |

